

MULČOVAČ BOMFORD TURBO MOWER

TECHNICKÉ PARAMETRY

Model	ELITE 130	ELITE 150	ELITE 190	ELITE 225	ELITE 245							PRO 270	PRO 3000
Pracovní záběr	1,3 m	1,45 m	1,9 m	2,26 m	2,42 m	2,72 m	2,5 m	2,8 m	2,44 m	2,77 m	2,45 m	2,7 m	3 m
Celková šířka	1,47 m	1,63 m	2,1 m	2,45 m	2,6 m	2,9 m	2,67 m	3 m	2,67 m	3 m	2,73 m	2,98 m	3,28 m
Hmotnost	213 kg	237 kg	451 kg	554 kg	596 kg	632 kg	867 kg	939 kg	859 kg	928 kg	1210 kg	1284 kg	1390 kg
Hydraulický posuv	-	-	ano	ano	ano	ano	ano	ano	ano	ano	ano	ano	ano
Posun od středu	-	-	400 mm	400 mm	400 mm	400 mm	500 mm	500 mm	500 mm	500 mm	400 mm	400 mm	400 mm
Rychlost PTO	540	540	540	540	540	1000	1000	1000	1000	1000	1000	1000	1000
Čelní agregace	-	-	-	-	-	-	ano	ano	-	-	ano	ano	ano
Počet kladiv	18	20	24	28	30	34	28	32	28	32	20	24	26
Min.výkon traktoru	30-37 HP	35-40 HP	45-60 HP	55-75 HP	65-90 HP	75-100 HP	65-110 HP	75-110 HP	65-100 HP	75-110 HP	68-80 HP	80-120 HP	90-135 HP
Výška sečení	32-111 mm	32-111 mm	32-111 mm	32-111 mm	32-111 mm	32-111 mm	43-88 mm	43-88 mm	32-111 mm	32-111 mm	45-157 mm	45-157 mm	45-157 mm



SYNPRO, s.r.o.

Podivínská 1559, Velké Bílovice

tel.: 733 376 775, E-mail: info@synpro.cz

www.synpro.cz

